

VP -480 Spring Check Valve (스프링 체크 밸브)

VP -490 Spring Foot Valve (스프링 후트 밸브)

- Specification : SCH,40
- To install by arrow indication
- Low cost / maintenance operation

- 규격 : Schedule 40
- 유체방향에 따라 화살표 표시대로 설치
- 역류방지설계 및 우수한 밀폐성

Type	Size	Standard	Material	Seal	Spring	End type
VP-480	1/2" ~ 2"	ANSI, JIS, DIN	PVC	EPDM, FPM	SUS 304	Socket, Threaded
VP-490	1/2" ~ 2"	ANSI, JIS, DIN	PVC	EPDM, FPM	SUS 304	Socket, Threaded



Nom.	SIZE	15mm	20mm	25mm	32mm	40mm	50mm
		(1/2")	(3/4")	(1")	(1-1/4")	(1-1/2")	(2")
JIS	d2	21.70	25.70	31.67	37.57	47.54	59.44
	d1	22.30	26.30	32.33	38.43	48.46	60.56
ANSI	d2	21.23	26.57	33.27	42.04	48.11	60.17
	d1	21.54	26.87	33.65	42.42	48.56	60.63
DIN	d2	19.9	24.9	31.9	39.9	49.9	62.9
	d1	20.3	25.3	32.3	40.3	50.3	63.3
thd./in	NPT	14	14	11.5	11.5	11.5	11.5
	BSPT	14	14	11	11	11	11
D		56	56	73	91	91	107
D1		35	35	45	52	60	73
D2		38	38	48	55	63	76
d		17	21	28	35	39	52
H		105	105	133	157	157	178
I	SCH40	17.48	18.26	22.22	23.82	27.38	29.36

NO.	PART	MATERIAL	Q'TY
1	UPPER BODY	UPVC	1
2	LOWER BODY	UPVC	1
3	SPIGOT	UPVC	1
4	CONNECTOR SEAT	UPVC	1
5	SPRING	SUS 304	1
6	SEAL	EPDM	1

Nom.	SIZE	15mm	20mm	25mm	32mm	40mm	50mm
		(1/2")	(3/4")	(1")	(1-1/4")	(1-1/2")	(2")
JIS	d2	21.70	25.70	31.67	37.57	47.54	59.44
	d1	22.30	26.30	32.33	38.43	48.46	60.56
ANSI	d2	21.23	26.57	33.27	42.04	48.11	60.17
	d1	21.54	26.87	33.65	42.42	48.56	60.63
DIN	d2	19.9	24.9	31.9	39.9	49.9	62.9
	d1	20.3	25.3	32.3	40.3	50.3	63.3
thd./in	NPT	14	14	11.5	11.5	11.5	11.5
	BSPT	14	14	11	11	11	11
D		60	60	83	83	110	124
D1		35	35	45	52	60	73
D2		38	38	48	55	63	76
d		17	21	28	35	39	52
H		123	123	147	170	170	198
I	SCH40	17.48	18.26	22.22	23.82	27.38	29.36

NO.	PART	MATERIAL	Q'TY
1	BODY	PVC	1
2	FILTER	PVC	1
3	SPIGOT	PVC	1
4	CONNECTOR SEAT	PVC	1
5	SPRING	SUS 304	1
6	SEAL	EPDM	1

