

# VP

-250 Blind Flanges (맹후렌지)

-260 One-piece [TS] Flanges (원피스[TS]후렌지)

-270 Two-piece [Van Stone] Flanges (투피스[반스톤]후렌지)

• Specification : JIS 10K / ANSI 150 LBS / DIN PN10 @73.4°F(23°C) Gasket Type

• 규격 : JIS 10K / ANSI 150LBS / DIN PN10 @73.4°F(23°C), 가스켓 접합 형식

Type	Size	Standard	Material	End type
VP-250	1/2" ~ 12"	ANSI, JIS, DIN	PVC	Flanged
VP-251	1/2" ~ 12"	ANSI, JIS, DIN	CPVC	Flanged
VP-260	1/2" ~ 12"	ANSI, JIS, DIN	PVC	Socket, Threaded / Flanged
VP-261	1/2" ~ 12"	ANSI, JIS, DIN	CPVC	Socket, Threaded / Flanged
VP-270	2" ~ 16"	ANSI	PVC	Socket, Threaded / Flanged
VP-271	2" ~ 16"	ANSI	CPVC	Socket, Threaded / Flanged

### BLIND FLANGE

Nom.	SIZE	15mm (1/2")	20mm (3/4")	25mm (1")	32mm (1-1/4")	40mm (1-1/2")	50mm (2")	65mm (2-1/2")	80mm (3")	100mm (4")	125mm (5")	150mm (6")	200mm (8")	250mm (10")	300mm (12")
ANSI	D	89	98	108	117	127	152	178	191	229	254	284	343	406	481
	D1	61	70	79	89	98	121	140	152	191	216	241	298	362	432
	T	12	13	14	16	17.5	19	22	24	24	28.5	26	28	34	34
	n-Øe	4-16	4-16	4-16	4-16	4-16	4-19	4-19	4-19	8-19	8-22	8-22	8-22	12-25	12-25
JIS	D	95	100	125	135	140	155	175	185	210	250	280	330	400	445
	D1	70	75	90	100	105	120	140	150	175	210	240	290	355	400
	T	14	15	15	16	16	20	22	22	22	24	26	28	30	30
	n-Øe	4-15	4-15	4-19	4-19	4-19	4-19	4-19	8-19	8-19	8-23	8-23	12-23	12-25	16-25



### ● BLIND FLANGE

